

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: HS Primer 4:1 Black

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: professional use.

Application of the substance / the mixture Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

R. Pohlmann GmbH
Pankower Str. 22
D-21502 Geesthacht
www.speedfinishes.com
Tel.: +49 (0)4152 88800

Further information obtainable from: msds@speedfinishes.com

1.4 Emergency telephone number:

+49 (0)551-19240 (Giftinformationszentrum-Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-15%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-<10%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-7.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-7.5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-2.5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.1-1%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	0.1-1%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

(Contd. on page 5)



**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 4)

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection**Additional information about design of technical facilities:**

No further data; see item 7.

(Contd. on page 6)

— EN —

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 5)

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****1330-20-7 xylene**

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
---------------------	---

1330-20-7 xylene

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

100-41-4 ethylbenzene

WEL (Great Britain)	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin

Regulatory information

WEL (Great Britain): EH40/2011

IOELV (EU): (EU) 2017/164

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 6)

DNELs		
123-86-4 n-butyl acetate		
Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)
1330-20-7 xylene		
Dermal	DNEL	180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	289 mg/m ³ (acute - systemic effects, workers) 289 mg/m ³ (acute - local effects, workers) 77 mg/m ³ (long-term - systemic effects, workers) 77 mg/m ³ (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	DNEL	153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	275 mg/m ³ (long-term - systemic effects, workers)
7779-90-0 trizinc bis(orthophosphate)		
Dermal	DNEL	83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1 mg/m ³ (long-term - systemic effects, workers)
1314-13-2 zinc oxide		
Dermal	DNEL	83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	5 mg/m ³ (long-term - systemic effects, workers)
100-41-4 ethylbenzene		
Dermal	DNEL	180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	293 mg/m ³ (acute - local effects, workers) 77 mg/m ³ (long-term - systemic effects, workers)
PNECs		
123-86-4 n-butyl acetate		
PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 35.6 mg/l (sewage treatment plants)	
PNEC	0.981 mg/kg (freshwater sediment environment)	

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 7)

1330-20-7 xylene	
PNEC	0.327 mg/l (freshwater environment) 6.58 mg/l (sewage treatment plants)
PNEC	12.46 mg/kg (freshwater sediment environment) 2.31 mg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC	3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment)
7779-90-0 trizinc bis(orthophosphate)	
PNEC	235.6 mg/kg (freshwater sediment environment) 113 mg/kg (marine sediment environment)
1314-13-2 zinc oxide	
PNEC	0.0206 mg/l (freshwater environment) 0.0061 mg/l (marine environment) 0.1 mg/l (sewage treatment plants)
PNEC	117.8 mg/kg (freshwater sediment environment) 56.5 mg/kg (marine sediment environment) 35.6 mg/kg (soil)
100-41-4 ethylbenzene	
PNEC	0.1 mg/l (freshwater environment) 0.01 mg/l (marine environment) 0.1 mg/l (intermittent releases) 9.6 mg/l (sewage treatment plants)
PNEC	13.7 mg/kg (freshwater sediment environment) 1.37 mg/kg (marine sediment environment) 2.68 mg/kg (soil)

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 8)

Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Regulatory information BMGV (Great Britain): EH40/2011

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

Filter A2/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Fluorocarbon rubber (Viton)

(Contd. on page 10)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 9)

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Highly viscous
Colour:	Different according to colouring
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point: $>23^{\circ}\text{C}$

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 10)

Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	15 Vol %
Vapour pressure at 20°C:	10.7 hPa
Density:	1.4-1.6 g/cm ³
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.

10.2 Chemical stability

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 11)

SECTION 11: Toxicological information
11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	10,760 mg/kg (rat) >14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

1330-20-7 xylene

Oral	ATE	>2,000 mg/kg
Dermal	ATE	1,466.67 mg/kg
Inhalative	ATE	12.09 mg/l (vapour)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/6 h	4,345 mg/l (rat)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

1314-13-2 zinc oxide

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

Primary irritant effect:
Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

(Contd. on page 13)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 12)

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.**Reproductive toxicity**

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****123-86-4 n-butyl acetate**

LC50/96 h	18 mg/l (Pimephales promelas)
TT/16 h	115 mg/l (Pseudomonas putida)
EC50/48 h	44 mg/l (daphnia)
EC50/72 h	675 mg/l (algae)

1330-20-7 xylene

LC50/96 h	2.6 mg/l (fish)
IC50/72 h	2.2 mg/l (algae)
EC50/48 h	>1-10 mg/l (Daphnia magna)
EC50/24 h	96 mg/l (microorganisms)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96 h	>100 mg/l (fish)
EC50/48 h	>500 mg/l (Daphnia magna)
EC20/30 min	>1,000 mg/l (microorganisms)
EC50/72 h	>1,000 mg/l (Pseudokirchnerella subcapitata)
EC50	>100 mg/l (Pseudokirchnerella subcapitata)
	>100 mg/l (Pimephales promelas)
	>100 mg/l (Daphnia magna)

(Contd. on page 14)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 13)

7779-90-0 trizinc bis(orthophosphate)	
EC50/3 h	5.2 mg/l (microorganisms)
EC50/48 h	>2.34 mg/l (Daphnia magna)
1314-13-2 zinc oxide	
LC50/96 h	4.92 mg/l (fish)
EC50/72 h	0.042 mg/l (Pseudokirchnerella subcapitata)
EC50/24 h	9.4 mg/l (microorganisms)
LC50/48 h	1.55 mg/l (Daphnia magna)
100-41-4 ethylbenzene	
EC50/48 h	2.4 mg/l (Daphnia magna)
EC20/30 min	200 mg/l (microorganisms)
EC50/24 h	13.4 mg/l (algae)
	7 mg/l (fish)
12.2 Persistence and degradability	
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
1330-20-7 xylene	
Biodegradation	>60 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
100-41-4 ethylbenzene	
Biodegradation	100 % (readily biodegradable) (OECD 301 E, 6 d, aerobic)
12.3 Bioaccumulative potential	
123-86-4 n-butyl acetate	
BCF	15.3 (-)
log Pow	2.3
1330-20-7 xylene	
BCF	25.9
log Pow	3.15
108-65-6 2-methoxy-1-methylethyl acetate	
log Pow	0.56
100-41-4 ethylbenzene	
BCF	1

(Contd. on page 15)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 14)

12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log Koc	1.27
108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7
100-41-4 ethylbenzene	
log Koc	2.41

Additional ecological information:**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG	1263 PAINT PAINT (trizinc bis(orthophosphate), hydrocarbons, C9-C12, n-alkanes,

(Contd. on page 16)

**Safety data sheet
according to 1907/2006/EC, Article 31**




Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 15)

IATA	isoalkanes, cyclics, aromatics (2-25%), MARINE POLLUTANT PAINT
14.3 Transport hazard class(es)	
ADR, IMDG	
 	
Class	3
Label	3
<hr style="border-top: 1px dashed black;"/>	
IATA	
	
Class	3
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Environmentally hazardous substance, liquid Product contains environmentally hazardous substances: trizinc bis(orthophosphate)
Marine pollutant (IMDG):	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S</u> -E
Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.	
Transport/Additional information:	
<hr style="border-top: 1px dashed black;"/>	
ADR	
Limited quantities (LQ)	5L

(Contd. on page 17)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 16)

Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

(Contd. on page 18)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2017

V- 1

Revision: 31.07.2017

Trade name: HS Primer 4:1 Black

(Contd. of page 17)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Sources European Chemicals Agency, <http://echa.europa.eu/>